

PROPERTIES	
Fibre	Coir
Fibre Content	100%
Fibre Characteristics	untreated, natural
Functional Longevity	30 – 40 months
Functional Longevity Wire Mesh	approx. 12-15 years
Weight / Total	~ 1100 g/m² +/- 10%
Weight / Fibre	~ 750 g/m ²
Blanket Thickness	10 – 15 mm
Bottom Netting Type	Light – PP
Bottom Netting Mesh Size	6 x 6 mm
Bottom Netting Weight	4,8 g/m ²
Inner Netting Type	Medium - PP
Inner Netting Mesh Size	12 x 13 mm
Inner Netting Weight	7,1 g/m ²
Stitching thread	PP-thread (brown), UV-degradable
Stitching thread tensile strength	6,5 cN/dtex
Slope recommendation	up to 75°
STANDARDS	
Tensile Strength EN ISO-10319	89,5 kg-force per 25 cm
Type	acc. to DIN 1200 – 0,8 mm wire
Size	25 x 25 mm, hexagon
Weight	350 g/m ²
Galvanized Coating	+/- 0,075 mm
Break Resistance	350 – 500 N/mm ²
SHIPPING & ORDER INFORMATION	
Part No.	O7D120
Width	1,20 m
Length	25 m
Area per Roll	30 m ²
Weight per Roll	30 kg
Diameter per Roll	0,47 m
Volume per Roll	0,27 m ³

We cannot warrant our products to perform under unlimited circumstances due variables such as soil conditions, manner of installation and particularly severe weather conditions. Satisfactory results may not meet your expectations. No one can guarantee that required moisture will occur to permit growth after seed germination. We will not be liable for damages or losses, direct or indirect, of our GREENFIX Range of Products due to the above reasons.

Latest-Update: May 8, 2017

Name: Kai Tietjen

File Name: ROCKMAT 7D

Copyright of these GREENFIX Document is reserved by SOILTEC GmbH. Copying or transmission of these document in whole or in part or any information contained therein is strictly prohibited without the prior authorization of SOILTEC GmbH, Germany.